

# Océ Specifications

## Océ Calendared PSA Gloss Vinyl - CALVIN6G

### Product Description

A 5.5 mil calendared gloss vinyl with a solvent based pressure sensitive adhesive back on a paper release liner. This version has a gloss, perfect for high detail and color pop. This product is designed for decals, stickers, and mounted signs. For added scratch resistance and durability laminate with a pressure sensitive over-laminating film. The solvent based adhesive will make a permanent bond with a smooth clean surface over time.

Profiles are available at [www.oceusa.com/imagingsupplies](http://www.oceusa.com/imagingsupplies).

### Physical Properties

Caliper		Smoothness	30 (Sheffield Units)
Vinyl and adhesive	5.5 mil	Opacity	95
Total	10 mil	Vinyl Type	Calendared
Gloss	65 @ 60°	Adhesive Type	Solvent
Whiteness	111 (We)		

### Printer Ink/Compatibility

Océ CALVIN6G is recommended for use in most solvent ink jet printers including:

Océ® Low Solvent	Océ® Eco Solvent ULTRA
Mimaki® ES3, SS2, SS2-1, HS	Hewlett-Packard® ECO-SOL
Roland® Eco-Sol Max	Mutoh® Eco Solvent ULTRA

### Available Sizes & Item Numbers

48" x 164' - CALVIN6G48

54" x 164' - CALVIN6G54

### Recommended Storage Conditions & Shelf Life

Temperature 59°-86°F. (15°-30°C). Relative Humidity 30-70%.  
Repack opened rolls when not in use.  
One year maximum at conditions noted above.  
Allow material to stabilize to room conditions 24 hours before use.

### Application Tips

Apply to smooth surfaces. For best results clean surface with an application fluid and thoroughly dry with a lint free cloth. Apply using the hinge method with a felt squeegee or roller so as not to damage or scratch your image. Apply even pressure working from the inside out.

### Océ Imaging Supplies

Product Info

*Display Graphics  
Solvent Media Line*

### Calendared PSA Gloss Vinyl

### CALVIN6G

**Solvent  
PSA VINYL**