

Océ Specifications



Océ Calendared PSA Matte Vinyl - CALVIN6M

Product Description

A 5.5 mil calendared matte vinyl with a solvent based pressure sensitive adhesive back on a paper release liner. This version has a matte finish, perfect for low glare. This product is designed for decals, stickers, and mounted signs. For added scratch resistance and durability laminate with a pressure sensitive overlaminating film. The solvent based adhesive will make a permanent bond with a smooth clean surface over time.

Profiles are available at www.oceusa.com/imagingsupplies.

Océ Imaging Supplies

Product Info

*Display Graphics
Solvent Media Line*

Physical Properties

| | | | |
|--------------------|----------|---------------|----------------------|
| <i>Caliper</i> | | Smoothness | 60 (Sheffield Units) |
| Vinyl and adhesive | 5.5 mil | Opacity | 95 |
| Total | 10 mil | Vinyl Type | Calendared |
| Gloss | 7 @ 60 ° | Adhesive Type | Solvent |
| Whiteness | 112 (We) | | |

Calendared PSA Matte Vinyl

CALVIN6M

Solvent
PSA VINYL

Printer Ink/ Compatibility

Océ CALVIN6M is recommended for use in most solvent ink jet printers including:

| | |
|-----------------------------|--------------------------|
| Océ® Low Solvent | Océ® Eco Solvent ULTRA |
| Mimaki® ES3, SS2, SS2-1, HS | Hewlett-Packard® ECO-SOL |
| Roland® Eco-Sol Max | Mutoh® Eco Solvent ULTRA |

Available Sizes & Item Numbers

48" x 164' - CALVIN6M48

54" x 164' - CALVIN6M54

Recommended Storage Conditions & Shelf Life

Temperature 59°-86°F. (15°-30°C). Relative Humidity 30-70%.
Repack opened rolls when not in use.
One year maximum at conditions noted above.
Allow material to stabilize to room conditions 24 hours before use.

Application Tips

Apply to smooth surfaces. For best results clean surface with an application fluid and thoroughly dry with a lint free cloth. Apply using the hinge method using a felt squeegee or roller so as not to damage or scratch your image. Apply even pressure working from the inside out.



<http://www.oceusa.com/imagingsupplies>
800-323-4827

© 2008 Océ

Illustrations and specifications do not necessarily apply to the standard version of machines in all local markets. Technical specifications subject to change without notice.

January, 2008